



For Low Voltage Circuit Control and Isolation - Incomers for Distribution Boards

- Conforms to IEC 60947-3/IS 13947 - 3
- Rated operational voltages 500V/690V
- Range 40A to 2500A
- Rated operational current @ AC 23A
- No deration upto 60° C
- Positive contact indication
- Common accessories with ComPact NSX/single auxillary contact
- Making capacity enhanced with ComPact NSX upstream

Pole Description	Rated Operational Current	Reference	Unit MRP ₹
------------------	---------------------------	-----------	---------------

Interpact Range of Switch Disconnectors

3-Pole	40 A AC-23A	28900	6680
	63 A AC-23A	28902	8070
	100 A AC-23A	28908	9520
	125 A AC-23A	28910	10380
	160 A AC-23A	28912	11550
	200 A AC-23A	31102	20090
	250 A AC-23A	31106	21210
	320 A AC-23A	31108	34550
	400 A AC-23A	31110	38920
4-Pole	630 A AC-23A	31114	40050
	40 A AC-23A	28901	7460
	63 A AC-23A	28903	8830
	100 A AC-23A	28909	10380
	125 A AC-23A	28911	11570
	160 A AC-23A	28913	12770
	200 A AC-23A	31103	22430
	250 A AC-23A	31107	23550
	320 A AC-23A	31109	40020
	400 A AC-23A	31111	41330
	630 A AC-23A	31115	46320

Interpact Changeover Systems (Complete Assembly)

3-Pole	100 A AC-23A	31140	64020
	160 A AC-23A	31144	69680
	200 A AC-23A	31142	76630
	250 A AC-23A	31146	78760
	320 A AC-23A	31148	130240
	400 A AC-23A	31150	139050
4-Pole	630 A AC-23A	31154	141460
	100 A AC-23A	31141	73020
	160 A AC-23A	31145	79850
	200 A AC-23A	31143	90430
	250 A AC-23A	31147	93570
	320 A AC-23A	31149	142050
	400 A AC-23A	31151	146660
	630 A AC-23A	31155	167900

Description	Reference	Unit MRP ₹
-------------	-----------	---------------

Accessories

Optional front extended rotary handle INS 250 - black handle (Switch Disconnector)	LV431050	5940
Optional front extended rotary handle INS 320..630 - black handle (Switch Disconnector)	31052	8390
Optional front extended rotary handle INS 40..160 - black handle (Switch Disconnector)	LV428941	3020
6 phase separators - INS100..160	28959	1330
6 phase separators - INS250	29329	1450
6 phase separators - INS400..630	LV432570	990

For details on non-standard references, technical parameters, stockable and non-stockable status, please contact Customer Care Centre.

☒ NORMAL STOCK ITEMS

W.E.F. January 30th, 2023



Fuse solutions from the world leader in electrical distribution

- The most complete fuse device offer in single and double break - switch disconnector fuses, fuse switch disconnectors and disconnector fuses
- Double break and Single break offer.
- Short-circuit and overload protection
- Isolation
- On-load switching of circuits

Range Details: NX range Switch Disconnecter Fuse

- 32A to 630A TP, TPN & FP version suitable for DIN/BS fuses.
- 4 break and 8 arcing zones
- IP20 Fuse protection cover is standard.

Range Details: ISFT range Fuse Switch Disconnecter

- 100A to 630A TP, version suitable for DIN fuses.
- Single breaking and direct connection to busbars
- isolation with positive contact indication when the fuse-carrier assembly is in the open position (OFF).

Range Details: ISFL range Vertical Fuse Switch Disconnecter

- 160A to 1250A TP, version suitable for DIN fuses.
- Single breaking and direct connection to busbars
- Two versions i.e Single pole or Three pole operation

- Complete Range from 32 to 630A in TP, TP+N & FP version suitable for DIN/BS fuses.
- 4 breaks and 8 arcing points
- IP20 Fuse Protection Cover is standard
- Higher Mechanical and Electrical life.

Without Enclosure

Rated Operational Current	Poles Description	DIN Type Reference	Unit MRP [₹]
32 A	3P + N	NX032TPNDI ☒	3450
63 A	3P + N	NX063TPNDI ☒	4580
80 A	3P + N	NX080TPNDI	8640
100 A	3P	NX100TPXDI	9620
	3P + N	NX100TPNDI ☒	9900
125 A	3P	NX125TPXDI ☒	11230
	3P + N	NX125TPNDI ☒	12150
160 A	3P + N	NX160TPNDI ☒	13250
200A	3P + N	NX200TPNDI ☒	17010
250 A	3P	NX250TPXDI	20050
	3P + N	NX250TPNDI ☒	20460
	4P	NX250FPXDI	24510
315 A	3P + N	NX315TPNDI ☒	25330
400 A	3P + N	NX400TPNDI ☒	34660
630 A	3P	NX630TPXDI	49740
	3P + N	NX630TPNDI ☒	50420

Accessories/Spares

Description	Reference	Unit MRP [₹]
NX032/NX063/NX080		
Auxiliary contact for FuPact	NXAA11 ☒	920
Handle operating mechanism (HOM) NX032...NX080	NXR1	670
NX100/NX125/NX160		
Auxiliary contact for FuPact	NXBA11 ☒	860
Fuse holder DIN for BS type NX100...NX160	NXHB21	330
Handle operating mechanism NX100...NX160	NXR2 ☒	1260
NX200		
Auxiliary contact for FuPact	NXBA11 ☒	860
Fuse holder for BS type NX200	NXHB22	340
Fuse holder for DIN NX200	NXHD22	390
Handle operating mechanism NX200	NXR2 ☒	1260
NX250/315/400		
Auxiliary contact for FuPact	NXBA11 ☒	860
Handle operating mechanism for NX250...NX400	NXR3	1300
NX630		
Auxiliary contact for FuPact	NXBA11 ☒	860

Note: For other versions please contact our nearest Sales Office.